



Elegance EL1003

Elegance EL1003 "16"

- The unit will:
 - be supplied by Vectaire Ltd
 - be a high performance, three speed axial fan
 - be suitable for **ALL** domestic wet rooms
 - be suitable for installation into wall, ceiling or window with appropriate accessories
 - have an air intake around the whole perimeter have a footprint no larger than 160 mm square
 - the casing should be constructed from shock-proof, high quality technopolymer.
 - will run continuously at pre-selected choice of two speeds (fixed at installation):
 - Speed 1 to operate at 8 l/sec
 - Speed 2 to operate at 17 l/sec
 speed can be boosted to maximum (26.7 l/sec) using integral pull cord or by:
 - remote switch/light switch
 - PIR sensor
 - DRH240 (dynamic remote humidistat)
 - have patented anti-turbulence deflectors to ensure very low noise levels and optimum performance
 - have EC induction motor with thermal protection
 - 43,000 hour life motors with maintenance free and long life ball bearings
 - thermal overload protection
 - operate in temperature up to 40°C
 - have a specific fan power from 0.09 W/l/s.
 - be IPX4 (splashproof) rated for safe installation in Zones I and II.
- The unit will:
 - be CE marked
 - comply with:
 - Building Regulations for enhanced energy saving capability
 - Building Regulations for reliable, efficient ventilation
 - EU RoHS Directive Compliant
 - IEC60335-2-80, LVD2006/95/CE and
 - EMC2014/30/UE (European Directive against radio interference and electro-magnetic compatibility)
 - be SAP PCDB Listed
 - be Energy Saving Trust Best Practice Compliant
 - have a 5 year warranty
- Please contact your Vectaire representative via Head Office on 01494 522333 for any assistance.
- An electronic copy of this specification is available on request.

Elegance EL1003

- The unit will:
 - be supplied by Vectaire Ltd
 - be a high performance, three speed axial fan
 - be suitable for **ALL** domestic wet rooms
 - be suitable for installation into wall, ceiling or window with appropriate accessories
 - have an air intake around the whole perimeter have a footprint no larger than 160 mm square
 - the casing should be constructed from shock-proof, high quality technopolymer.
 - will run continuously at pre-selected choice of two speeds (fixed at installation):
 - Speed 1 to operate at 8 l/sec
 - Speed 2 to operate at 13.6 l/sec
 speed can be boosted to maximum (28.5 l/sec) using integral pull cord or by:
 - remote switch/light switch
 - PIR sensor
 - DRH240 (dynamic remote humidistat)
 - have patented anti-turbulence deflectors to ensure very low noise levels and optimum performance
 - have EC induction motor with thermal protection
 - 43,000 hour life motors with maintenance free and long life ball bearings
 - thermal overload protection
 - operate in temperature up to 40°C
 - have a specific fan power from 0.09 W/l/s.
 - be IPX4 (splashproof) rated for safe installation in Zones I and II
- The unit will:
 - be CE marked
 - comply with:
 - Building Regulations for enhanced energy saving capability
 - Building Regulations for reliable, efficient ventilation
 - EU RoHS Directive Compliant
 - IEC60335-2-80, LVD2006/95/CE and
 - EMC2014/30/UE (European Directive against radio interference and electro-magnetic compatibility)
 - be SAP PCDB Listed
 - be Energy Saving Trust Best Practice Compliant
 - have a 5 year warranty
- Please contact your Vectaire representative via Head Office on 01494 522333 for any assistance.
- An electronic copy of this specification is available on request.